


Mini slide unit EGSS-BS-KF-32-25-8P-ST-M-H1-PLK-AA

Part number: 8083801

FESTO



Data sheet

Feature	Value
KC characters	KC EMC
Additional functions	User interface Integrated end-position sensing
Switching logic at outputs	PNP (positive switching)
Shock resistance	Shock test with severity level 1 as per FN 942017-5 and EN 60068-2-27
Vibration resistance	Transport application test with severity level 1 as per FN 942017-4 and EN 60068-2-6
Relative air humidity	0 - 90 %
Characteristics of digital logic outputs	Configurable Not galvanically isolated
Rotor position sensor	Absolute encoder, single-turn
Insulation protection class	B
Logic input specification	Based on IEC 61131-2, type 1
Parameterization interface	IO-Link® User interface
Characteristics of logic input	Configurable Not galvanically isolated
Ready status indication	LED
Max. cable length	15 m outputs 15 m inputs 20 m for IO-Link® operation
Display	LED
Input switching logic	PNP (positive switching)
Note on ambient temperature	Above an ambient temperature of 30°C, the power must be reduced by 2% per K.
Rotor position sensor measuring principle	Magnetic
Permissible voltage fluctuations	+/- 15 %
Logic interface, connection pattern	00992264
Power supply, type of connection	Plug
Logic interface, connection type	Plug
Power supply, connection pattern	00995989
Power supply, connection technology	M12x1, T-coded as per EN 61076-2-111
Logic interface, connection technology	M12x1, A-coded as per EN 61076-2-101
Number of digital logic inputs	2
Number of digital logic outputs 24 V DC	2
Logic interface, number of poles/wires	8
DC nominal voltage	24 V
Power supply, number of pins/wires	4

Feature	Value
Max. current of digital logic outputs	100 mA
Storage temperature	-20 °C ... 60 °C
Max. current consumption	3000 mA
Rotor position sensor resolution	16 bit
Nominal current	3 A
Work range of logic input	24 V
IO-Link®, Connection technology	Plug
IO-Link®, number of ports	1
IO-Link®, communication mode	COM3 (230.4 kBd)
IO-Link®, protocol version	Device V 1.1
IO-Link®, port class	A
IO-Link®, process data width IN	2 Byte
IO-Link®, service data contents IN	32 bit force 32 bit position 32 bit speed
IO-Link®, minimum cycle time	1 ms
IO-Link®, process data content OUT	1 bit (move in) 1 bit (move out) 1 bit (quit error)
Protection class	III
IO-Link®, process data width OUT	2 Byte
IO-Link®, SIO mode support	Yes
IO-Link®, process data content IN	1 bit (state device) 1 bit (state move) 1 bit (state in) 1 bit (state out)
IO-Link®, data memory required	500 byte
Working stroke	25 mm
Size	32
Stroke reserve	0 mm
Reversing backlash	150 µm
Screw diameter	8 mm
Spindle pitch	8 mm/U
Type code	EGSS
Mounting position	Any
Guide	Recirculating ball bearing guide
Design	Electrical mini-slide with ball screw drive With integrated drive
Motor type	Stepper motor
Homing	Fixed stop block positive Fixed stop block, negative Reference switch
Spindle type	Ball screw drive
Symbol	00997294
Position sensing	Motor encoder For proximity sensor
Max. acceleration	5 m/s²
Max. speed	0.19 m/s
Repetition accuracy	±0.015 mm
Duty cycle	100%
CE marking (see declaration of conformity)	As per EU EMC directive As per EU RoHS directive
Corrosion resistance class (CRC)	0 - No corrosion stress
Degree of protection	IP40
Ambient temperature	0 °C ... 50 °C

Feature	Value
Certification	RCM compliance mark
Fixed bearing dynamic basic load rating	3795 N
Linear guide dynamic basic load rating	2135 N
Dynamic basic load rating, ball screw drive	2000 N
Max. force Fy	991 N
Max. force Fz	991 N
Max. torque Mx	3.4 Nm
Max. torque My	3.17 Nm
Max. torque Mz	3.17 Nm
Max. radial force on actuator shaft	140 N
Max. feed force Fx	60 N
Guide value for payload, horizontal	2 kg
Guide value for payload, vertical	2 kg
Ball screw drive statistical basic load rating	3700 N
Linear guide statistical basic load rating	3880 N
Feed constant	8 mm/U
Statistical fixed bearing load rating	1792 N
Reference value, running performance	5000 km
Maintenance interval	Life-time lubrication
Moving mass at 0 mm stroke	149 g
Additional weight per 10 mm stroke	30 g
Basic weight with 0 mm stroke	924 g
Product weight	999 g
Additional moving mass per 10 mm stroke	12 g
Type of mounting	With internal thread With centering sleeve With accessories With cylindrical pin
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Slide carriage material	Roller bearing steel
Guide rail material	Roller bearing steel
Housing material	Wrought aluminum alloy, anodized
Material of yoke plate	Wrought aluminum alloy, anodized
Piston rod material	High-alloy stainless steel
Slide material	Wrought aluminum alloy, anodized
Spindle nut material	Roller bearing steel
Spindle material	Roller bearing steel