



# Air solenoid valve CPE24-M3H-5JS-3/8

Part number: 163839

**FESTO**



## Data sheet

| Feature                                  | Value  |
|--|--|
| Valve function                           | 5/2, bistable  |
| Maritime classification                  | See certificate  |
| Lap                                      | Overlap  |
| Actuation type                           | Electrical   |
| Width                                    | 24 mm  |
| Standard nominal flow rate               | 3200 l/min   |
| Pneumatic working port                   | G3/8   |
| Operating voltage                        | 230V AC  |
| Operating pressure                       | -0.9 bar ... 10 bar  |
| Design                                   | Piston gate valve  |
| Degree of protection                     | IP65<br>With plug socket<br>as per IEC 60529   |
| Certification                            | c UL us - Recognized (OL)  |
| Nominal width                            | 11 mm  |
| Type code                                | CPE24  |
| Exhaust air function                     | With flow control option   |
| Sealing principle                        | Soft   |
| Mounting position                        | Any  |
| Manual override                          | Detenting via accessory<br>Non-detenting   |
| Type of control                          | Pilot-controlled   |
| Pilot air supply port                    | External   |
| Flow direction                           | Reversible   |
| Symbol                                   | 00991016   |
| Valve position ID                        | Label holder   |
| Pilot pressure                           | 2 bar ... 10 bar   |
| Changeover time                          | 25 ms  |
| Duty cycle                               | 100%   |
| Max. positive test pulse with 0 signal   | 3300 µs  |
| Max. negative test pulse on 1 signal     | 3100 µs  |
| Coil characteristics                     | 230 V AC: 50/60 Hz, initial power 3.0 VA, holding power 2.4 VA                       |
| Permissible voltage fluctuations         | -15 % / +10 %  |
| Operating medium                         | Compressed air as per ISO 8573-1:2010 [7:4:4]  |
| Information on operating and pilot media | Operation with oil lubrication possible (required for further use)                   |
| Vibration resistance                     | Transport application test with severity level 2 as per FN 942017-4 and EN 60068-2-6 |

| Feature                          | Value   |
|----------------------------------|---|
| Shock resistance                 | Shock test with severity level 2 as per FN 942017-5 and EN 60068-2-27 |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress   |
| Temperature of medium            | -5 °C ... 50 °C   |
| Pilot medium                     | Compressed air as per ISO 8573-1:2010 [7:4:4]                         |
| Ambient temperature              | -5 °C ... 50 °C   |
| Product weight                   | 390 g   |
| Electrical connection            | Form C  |
| Type of mounting                 | With through-hole   |
| Pilot exhaust air port 82        | M5  |
| Pilot exhaust air port 84        | M5  |
| Pilot air port 12                | M5  |
| Pilot air port 14                | M5  |
| Pneumatic connection 1           | G3/8  |
| Pneumatic connection 2           | G3/8  |
| Pneumatic connection 3           | G3/8  |
| Pneumatic connection 4           | G3/8  |
| Pneumatic connection 5           | G3/8  |
| Note on materials                | RoHS-compliant  |
| Seals material                   | NBR   |
| Housing material                 | Die-cast aluminum   |