


# Vacuum suction cup ESS-150-SF

Part number: 189329

FESTO



## Data sheet

| Feature                                     | Value  |
|---|--|
| Min. workpiece radius                       | 480 mm   |
| Nominal width                               | 10 mm  |
| Suction cup diameter                        | 150 mm   |
| Suction cup volume                          | 173.826 cm <sup>3</sup>  |
| Type code                                   | ESS  |
| Connection position                         | Top  |
| Mounting position                           | Any  |
| Symbol                                      | 00991485   |
| Classification of suction cup holder        | Size 6   |
| Suction cup shape                           | Round, flat  |
| Operating pressure                          | 0 bar ... 0.95 bar   |
| Nominal operating pressure                  | -0.7 bar   |
| Operating medium                            | Atmospheric air based on ISO 8573-1:2010 [7:::]                    |
| Corrosion resistance class (CRC)            | 1 - Low corrosion stress   |
| For use in the food industry                | See supplementary material information                             |
| Ambient temperature                         | -10 °C ... 200 °C  |
| Holding force at nominal operating pressure | 900 N  |
| Lateral force at nominal operating pressure | 480 N  |
| Product weight                              | 719 g  |
| Type of mounting                            | Via vacuum connection  |
| Vacuum connection                           | M20x2  |
| Color                                       | Gray   |
| Shore hardness                              | 60 +/- 5   |
| Material of screwed trunnion                | NBR<br>Steel, nickel-plated<br>Steel, galvanized and chrome-plated |
| Note on materials                           | Free of copper and PTFE<br>RoHS-compliant                          |
| Suction cup material                        | FPM  |