
Filter regulator LFR-1/4-DB-7-MINI Part number: 539685

FESTO





Data sheet

| Feature | Value |
|----------------------------------|---|
| Size | Mini |
| Width | 44 mm |
| Type code | LFR |
| Series | DB |
| Actuator lock | Rotary knob with detent |
| Mounting position | Vertical +/- 5° |
| Grade of filtration | 40 μm |
| Condensate drain | Manually rotating |
| Design | Filter regulator with pressure gauge |
| Controller function | With secondary exhausting With return flow function |
| Symbol | 00991589 |
| Pressure gauge | with pressure gauge |
| Operating pressure | 1.5 bar 10 bar |
| Operating pressure | 0.15 MPa 1 MPa |
| Pressure regulation range | 0.5 bar 7 bar |
| Max. pressure hysteresis | 0.5 bar |
| Standard nominal flow rate | ≥1200 l/min |
| Operating medium | Compressed air as per ISO 8573-1:2010 [-:9:-] Inert gas |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| Air quality class at the output | Compressed air as per ISO 8573-1:2010 [7:8:4] Inert gas |
| Temperature of medium | -5 °C 50 °C |
| Ambient temperature | -5 °C 50 °C |
| Product weight | 200 g |
| Type of mounting | Optionally: Line installation With through-hole With mounting bracket |
| Pressure gauge connection | G1/8 |
| Pneumatic connection 1 | G1/4 |
| Pneumatic connection 2 | G1⁄4 |
| Note on materials | RoHS-compliant |
| Seals material | NBR |
| Rotary knob material | POM |
| Compressed air filter material | PE |

| Feature | Value |
|------------------|---------------|
| Housing material | PA-reinforced |
| Material of bowl | PC |