

# Linear actuator DFPC-80-65-D

Part number: 8110817

**FESTO**



## Data sheet

Feature	Value
Size of valve actuator	80
Impact energy in the end positions	1.4 J
Shock resistance	Shock test with severity level 1 as per FN 942017-5 and EN 60068-2-27
Vibration resistance	Transport application test with severity level 1 as per FN 942017-4 and EN 60068-2-6
Operating pressure	0.06 MPa ... 0.8 MPa
Nominal operating pressure	87 psi
Nominal operating pressure	0.6 MPa
Operating pressure	8.7 psi ... 116 psi
Flange hole pattern	F07
Stroke	65 mm
Piston diameter	80 mm
Type code	DFPC
Standard connection for valve	ISO 5210
Cushioning	Elastic cushioning rings/pads at both ends
Mounting position	Any
Mode of operation	Double-acting
Design	Piston Piston rod Tie rod Cylinder barrel
Position sensing	For proximity sensor
Symbol	00991217
Operating pressure	0.6 bar ... 8 bar
Nominal operating pressure	6 bar
Ambient temperature	-20 °C ... 80 °C
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Theoretical force at 6 bar, retracting	2827 N
Theoretical force at 6 bar, advancing	3016 N
Air consumption, retracting, per 10 mm stroke	0.33 l
Air consumption advancing per 10 mm stroke	0.352 l
Moving mass at 0 mm stroke	451 g
Additional weight per 10 mm stroke	61.8 g
Basic weight with 0 mm stroke	1230.3 g
Product weight	1630 g
Additional moving mass per 10 mm stroke	24.8 g

Feature	Value
Type of mounting	Optionally: On flange as per ISO 5210 With spacer bolt
Pneumatic connection	G1/8
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Cover material	Gravity die-cast aluminum
Piston rod material	High-alloy stainless steel
Piston rod wiper seal material	TPE-U(PU)
Nut material	High-alloy stainless steel
Static seal material	NBR
Tie rod material	High-alloy stainless steel
Material of cylinder barrel	Wrought aluminum alloy, smooth-anodized