

Push-in T-fitting CRQST-3/8-3/8-U

FESTO

Part number: 565339



Data sheet

| Feature | Value |
|---|--|
| Size | Standard |
| Type of mounting | External hexagon 45/64 |
| Design | T-shape |
| Nominal width | 8.509 mm |
| Type code | CRQST |
| Mounting position | Any |
| Pack size | 1 |
| Design | Push-pull principle |
| Operating pressure for entire temperature range | -0.951 bar ... 14.003 bar |
| Operating medium | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| Corrosion resistance class (CRC) | 4 - Particularly high corrosion stress |
| For use in the food industry | See supplementary material information |
| Ambient temperature | -20 °C ... 150 °C |
| Max. tightening torque | 18 Nm |
| Product weight | 66.509 g |
| Usable connector cables | PFAN |
| Pneumatic connection 1 | Male thread 3/8 NPTF |
| Pneumatic connection 2 | for pneumatic tubing outside diameter 3/8" |
| Note on materials | Contains paint-wetting impairment substances RoHS-compliant |
| Housing material | High-alloy stainless steel |
| Releasing ring material | High-alloy stainless steel |
| Material of tubing seal | FPM |
| Material of tube retaining claw | High-alloy stainless steel |