



Proximity sensor SIEH-M18B-PS-S-L-CR

Part number: 538255

FESTO



Data sheet

| Feature | Value |
|--|--|
| Type code | SIEH |
| Conforms to standard | EN 60947-5-2 |
| Symbol | 00991701 |
| Certification | RCM compliance mark c UL us - Listed (OL) |
| CE marking (see declaration of conformity) | As per EU EMC directive |
| Note on materials | Free of copper and PTFE |
| Rated operating distance | 10 mm |
| Assured operating distance | 8.1 mm |
| Reduction factors | Aluminum = 1.0 Stainless steel, 1 mm thick = 0.4 Stainless steel, 2 mm thick = 0.8 Copper = 0.8 Brass = 1.3 Steel St 37 = 1.0 |
| Ambient temperature | -25 °C ... 70 °C |
| Switching output | PNP |
| Switching element function | N/O contact |
| Reproducibility, switching value FS | 0.5 mm |
| Hysteresis | ≤1.22 mm |
| Max. switching frequency | 200 Hz |
| Max. output current | 200 mA |
| Voltage drop | 2 V |
| Inductive protective circuit | Installed Output current < 100 mA and switching frequency < 10 Hz |
| Short-circuit protection | Pulsed |
| DC operating voltage range | 10 V ... 30 V |
| Residual ripple | 20 % |
| Idle current | <12 mA |
| Reverse polarity protection | for all electrical connections |
| Electrical connection | 3-pin M12x1 Plug |
| Size | M18 |
| Type of mounting | With lock nut |
| Mounting type | Flush |
| Product weight | 53 g |

| Feature | Value |
|--|-----------------------------------|
| Housing material | High-alloy steel |
| Switching status indication | LED yellow |
| Ambient temperature with flexible cable installation | -5 °C ... 70 °C |
| Degree of protection | IP67 IP69K |
| Resistance to sensor fitting pressure | 60 bar |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| Selection of additional sensor information | With increased switching distance |
| Electrical output | PNP |
| Selection of sensor version | Fully stainless steel housing |