

Servo motor EMME-AS-60-M-LS-ASB

Part number: 2089732

FESTO



Data sheet

Feature	Value
Number of pole pairs	3
Type code	EMME-AS
Rotor position sensor	Absolute encoder, single-turn
Rotor position sensor interface	HIPERFACE®
Rotor position sensor measuring principle	Capacitive
Max. rotational speed	4925 1/min
Nominal rotary speed	3000 1/min
Brake DC operating voltage	24 V
Continuous stall current	1.8 A
Insulation protection class	F
Brake power consumption	11 W
Motor constants	0.8 Nm/A
Nominal operating voltage DC	360 V
Motor nominal power	380 W
DC nominal voltage	360 V
Motor nominal current	1.5 A
Typical rotor position sensor resolution	12 bit
Rotor position encoder, typical angular accuracy	20 arcmin
Rotor position encoder, sinusoidal/cosinusoidal periods per revolution	16
Phase-phase winding resistance	9.8 Ohm
Winding inductance phase-phase	16.8 mH
Type of winding switch	Star inside
Peak current	7.2 A
Voltage constant, phase-to-phase	51.7 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive
Corrosion resistance class (CRC)	0 - No corrosion stress
Storage temperature	-20 °C ... 70 °C
Relative air humidity	0 - 90 %
Degree of protection	IP21
Ambient temperature	-10 °C ... 40 °C
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	0.512 kgcm ²
Brake holding torque	2 Nm

Feature	Value
Brake mass moment of inertia	0.086 kgcm ²
Nominal torque	1.2 Nm
Peak torque	6 Nm
Stall torque	1.5 Nm
Permissible axial shaft load	54 N
Permissible radial shaft load	270 N
MTTF, subcomponent	538 years, holding brake
MTTFd, subcomponent	340 years, rotor position sensor
Switching cycles, holding brake	5 million idle actuations (without friction work!)
Product weight	2200 g
Electrical connection technology	Plug
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Conforms to standard	IEC 60034