

**Ball valve**  
**VZBE-1/2-T-63-D-2-M-V15V15**  
Part number: 4745216

**FESTO**



**Data sheet**

| Feature                       | Value                            |
|-------------------------------|----------------------------------|
| Type code                     | VZBE                             |
| Seat seal material            | PTFE                             |
| Design                        | 2-way ball valve with hand lever |
| Actuation type                | Mechanical                       |
| Sealing principle             | Soft                             |
| Mounting position             | Any                              |
| Type of mounting              | Line installation                |
| Fitting connection            | 1/2 NPT                          |
| Switching position indication | Slot direction = flow direction  |
| Inside diameter               | 15 mm                            |
| Nominal width DN              | 15                               |
| Valve function                | 2/2                              |
| Flow direction                | Reversible                       |

| Feature                                                                 | Value                                                                                          |
|-------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| Nominal pressure of fitting PN                                          | 63                                                                                             |
| Breakaway torque at differential pressure, nominal pressure, fitting PN | 5.5 Nm                                                                                         |
| Based on norm                                                           | ASME B1.20.1                                                                                   |
| Symbol                                                                  | 00991458                                                                                       |
| Medium                                                                  | Vapor<br>Compressed air as per ISO 8573-1:2010 [:-:-]<br>Inert gas<br>Water<br>Neutral liquids |
| Temperature of medium                                                   | -20 °C ... 200 °C                                                                              |
| Flow rate Kv                                                            | 8.5 m³/h                                                                                       |
| Note on materials                                                       | Contains paint-wetting impairment substances<br>RoHS-compliant                                 |
| Housing material                                                        | Cast stainless steel                                                                           |
| Material number of housing                                              | 1.4408                                                                                         |
| Seals material                                                          | PTFE                                                                                           |
| Ball material                                                           | Cast stainless steel                                                                           |
| Material number for ball                                                | 1.4408                                                                                         |
| Shaft material                                                          | High-alloy stainless steel                                                                     |
| Material number for shaft                                               | 1.4401                                                                                         |
| Product weight                                                          | 300 g                                                                                          |
| Certification                                                           | CRN                                                                                            |
| Corrosion resistance class (CRC)                                        | 3 - High corrosion stress                                                                      |
| Explosion prevention and protection                                     | Zone 1 (ATEX)<br>Zone 2 (ATEX)<br>Zone 21 (ATEX)<br>Zone 22 (ATEX)                             |