

# Push-in T-fitting NPQM-T-G38-Q12-P10

FESTO

Part number: 558745



## Data sheet

| Feature                                         | Value                                         |
|-------------------------------------------------|-----------------------------------------------|
| Size                                            | Standard                                      |
| Nominal width                                   | 11 mm                                         |
| Type code                                       | NPQM-T                                        |
| Type of seal on screwed trunnion                | Sealing ring                                  |
| Design                                          | Push-pull principle                           |
| Operating pressure for entire temperature range | -0.95 bar ... 16 bar                          |
| Operating medium                                | Compressed air as per ISO 8573-1:2010 [7:-:-] |
| Information on operating and pilot media        | Operation with oil lubrication possible       |
| Corrosion resistance class (CRC)                | 1 - Low corrosion stress                      |
| Ambient temperature                             | -20 °C ... 70 °C                              |
| Nominal tightening torque                       | 9 Nm                                          |
| Tolerance for nominal tightening torque         | ± 20%                                         |
| Product weight                                  | 75.3 g                                        |
| Pneumatic connection 1                          | G3/8                                          |
| Pneumatic connection 2                          | for pneumatic tubing outside diameter 12 mm   |
| Note on materials                               | RoHS-compliant                                |
| Housing material                                | Brass, nickel-plated                          |
| Material of tubing seal                         | NBR                                           |