

# Push-in fitting QS-G3/4-22

Part number: 8040613

**FESTO**



## Data sheet

Feature	Value
Size	Standard
Nominal width	20 mm
Type code	QS
Type of seal on screwed trunnion	Sealing ring
Mounting position	Any
Pack size	1
Design	Push-pull principle
Operating pressure for entire temperature range	-0.95 bar ... 14 bar
Temperature-dependent operating pressure	-0.95 bar ... 14 bar
Operating medium	Compressed air as per ISO 8573-1:2010 [7:-:] Water as per manufacturer's declaration at <a href="http://www.festo.com">www.festo.com</a>
Information on operating and pilot media	Operation with oil lubrication possible
Corrosion resistance class (CRC)	1 - Low corrosion stress
Ambient temperature	-20 °C ... 80 °C
Nominal tightening torque	20 Nm
Tolerance for nominal tightening torque	± 20%
Product weight	93.2 g
Pneumatic connection 1	External thread G3/4
Pneumatic connection 2	for pneumatic tubing outside diameter 22 mm
Releasing ring color	Blue
Note on materials	RoHS-compliant
Housing material	Brass Nickel-plated
Releasing ring material	POM
Material of tubing seal	NBR
Material of tube retaining claw	High-alloy stainless steel