


Servo motor EMME-AS-80-M-LS-AMXB

Part number: 4267589

FESTO



Data sheet

Feature	Value
Number of pole pairs	3
Type code	EMME-AS
Rotor position sensor	Safety encoder, absolute multi-turn
Rotor position sensor interface	HIPERFACE®
Rotor position sensor measuring principle	Optical
Safety Integrity Level (SIL), subcomponent	SIL 2, rotor position sensor SILCL 2, rotor position sensor
Performance Level (PL), subcomponent	Category 3, performance level d, rotor position encoder
PFHd, subcomponent	1.3 x 10E-8, rotor position sensor
Duration of use Tm, subcomponent	20 years, rotor position sensor
Max. rotational speed	4627 1/min
Nominal rotary speed	3000 1/min
Brake DC operating voltage	24 V
Continuous stall current	3.9 A
Insulation protection class	F
Brake power consumption	12 W
Motor constants	0.865 Nm/A
Nominal operating voltage DC	360 V
Motor nominal power	1000 W
DC nominal voltage	360 V
Motor nominal current	3.7 A
Typical rotor position sensor resolution	15 bit
Rotor position encoder, typical angular accuracy	20 arcmin
Rotor position encoder, sinusoidal/cosinusoidal periods per revolution	128
Phase-phase winding resistance	2.8 Ohm
Winding inductance phase-phase	7.43 mH
Type of winding switch	Star inside
Peak current	15.6 A
Voltage constant, phase-to-phase	55 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive
Corrosion resistance class (CRC)	0 - No corrosion stress
Storage temperature	-20 °C ... 70 °C
Relative air humidity	0 - 90 %
Degree of protection	IP21

Feature	Value
Ambient temperature	-10 °C ... 40 °C
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	2.2 kgcm ²
Brake holding torque	4.5 Nm
Brake mass moment of inertia	0.222 kgcm ²
Nominal torque	3.2 Nm
Peak torque	14 Nm
Stall torque	3.5 Nm
Permissible axial shaft load	72 N
Permissible radial shaft load	360 N
MTTF, subcomponent	797 years, holding brake
MTTFd, subcomponent	874 years, rotor position sensor
Switching cycles, holding brake	5 million idle actuations (without friction work!)
Product weight	4350 g
Electrical connection technology	Plug
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Conforms to standard	IEC 60034