


Three-point gripper DHDS-16-A-NC

Part number: 1259492

FESTO



Data sheet

Feature	Value
Size	16
Stroke per gripper jaw	2.5 mm
Max. interchangeability	≤0.2 mm
Max. gripper jaw angular play ax, ay	≤0.5 deg
Max. gripper jaw backlash Sz	≤0.02 mm
Rotational symmetry	≤0.2 mm
Pneumatic gripper repetition accuracy	≤0.04 mm
Type code	DHDS
Number of gripper jaws	3
Mounting position	Any
Mode of operation	Double-acting
Gripper function	3-point
Gripping force backup	During closing
Design	Lever Positively driven motion sequence
Position sensing	For Hall sensor
Symbol	00995947
Operating pressure	4 bar ... 8 bar
Max. operating frequency of pneumatic gripper	≤4 Hz
Min. opening time at 6 bar	31 ms
Min. closing time at 6 bar	34 ms
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	1 - Low corrosion stress
Ambient temperature	5 °C ... 60 °C
Mass moment of inertia	0.139 kgcm ²
Maximum force on gripper jaw Fz, static	50 N
Maximum torque on gripper jaw, Mx static	2 Nm
Maximum torque on gripper jaw, My static	2 Nm
Maximum torque on gripper jaw, Mz static	2 Nm
Relubrication interval for guidance elements	10 MioCyc
Max. mass per external gripper finger	50 g
Product weight	99 g
Type of mounting	With internal thread and dowel pin
Pneumatic connection	M3
Note on materials	RoHS-compliant

Feature	Value
Cover cap material	PA
Housing material	Wrought aluminum alloy Hard-anodized
Gripper jaw material	High-alloy stainless steel