


# Parallel gripper HGPT-63-A-B-F-G1

Part number: 560232

FESTO



## Data sheet

| Feature                                       | Value  |
|---|--|
| Size  | 63   |
| Stroke per gripper jaw                        | 8 mm   |
| Max. interchangeability                       | ≤0.2 mm  |
| Max. gripper jaw angular play ax, ay          | ≤0.1 deg   |
| Max. gripper jaw backlash Sz                  | ≤0.02 mm   |
| Rotational symmetry                           | ≤0.2 mm  |
| Pneumatic gripper repetition accuracy         | ≤0.05 mm   |
| Type code                                     | HGPT   |
| Number of gripper jaws                        | 2  |
| Mounting position                             | Any  |
| Mode of operation                             | Double-acting  |
| Gripper function                              | Parallel   |
| Gripping force backup                         | On opening   |
| Design  | Inclined plane<br>Positively driven motion sequence                |
| Position sensing                              | For proximity sensor   |
| Symbol  | 00995947   |
| Operating pressure                            | 4 bar ... 8 bar  |
| Operating pressure for sealing air            | 0 bar ... 0.5 bar  |
| Max. operating frequency of pneumatic gripper | ≤2 Hz  |
| Min. opening time at 6 bar                    | 145 ms   |
| Min. closing time at 6 bar                    | 315 ms   |
| Operating medium                              | Compressed air as per ISO 8573-1:2010 [7:4:4]                      |
| Information on operating and pilot media      | Operation with oil lubrication possible (required for further use) |
| Corrosion resistance class (CRC)              | 2 - Moderate corrosion stress                                      |
| Degree of protection                          | IP40   |
| Ambient temperature                           | 5 °C ... 60 °C   |
| Mass moment of inertia                        | 93.034 kgcm <sup>2</sup>   |
| Maximum force on gripper jaw Fz, static       | 5000 N   |
| Maximum torque on gripper jaw, Mx static      | 160 Nm   |
| Maximum torque on gripper jaw, My static      | 180 Nm   |
| Maximum torque on gripper jaw, Mz static      | 140 Nm   |
| Relubrication interval for guidance elements  | 5 MioCyc   |
| Max. mass per external gripper finger         | 1260 g   |
| Product weight                                | 3562 g   |

| Feature                          | Value  |
|----------------------------------|--|
| Type of mounting                 | Optionally:<br>With internal thread and centering sleeve<br>Via through-hole and centering sleeve<br>With through-hole and dowel pin<br>With internal thread and dowel pin |
| Sealing air pneumatic connection | M5   |
| Pneumatic connection             | G1/8   |
| Note on materials                | Free of copper and PTFE<br>RoHS-compliant  |
| Cover cap material               | High-alloy stainless steel   |
| Housing material                 | Aluminum<br>Anodized   |
| Gripper jaw material             | Steel<br>Hardened  |