

Panel Interface Connectors

PIC Accessories



Low Profile Single Port Shell | M25 Threads

UL Type 12

IP65, IP69 Rating



Mencom port adapters are available in a low profile black plastic shell with a M25 mounting thread. These port adapters have a RJ45, USB Type A, or USB Type B connector, and can easily be mounted to a cabinet through a 1" diameter hole. A cap is supplied with each unit to make them suitable for wash down.

| Part Number | Description | Front | Back | Cutout |
|--------------------|---------------------------------------|---|---|---|
| RJ12-M25-PA | RJ45 Jack to RJ45 Jack | - - 0 | O | |
| RJ45-M25-PA | RJ45 Jack to RJ45 Jack | | | |
| RJ45S-M25-PA | RJ45 Jack to RJ45 Jack with Shield | | | - [23.2] .91 |
| D-USB-AFAF-M25-PA | USB Female TYPE A to Female TYPE A | | | [25.2] Ø.99 |
| D-USB-AFBF-M25-PA | USB Female TYPE A to Female TYPE B | | | Tightening Torque: 5.0 N-m Max. Panel Thickness: 15 mm |
| D-USB-BFBF-M25-PA | USB Female TYPE B to Female TYPE B | | | |
| D-USB-BFAF-M25-PA | USB Female TYPE B to Female TYPE A | | | |
| RJ45 Port Adapters | [99] 3.9 | RJ45 JACK [32.0] Ø1.26 [8.5] .33 [23.8] .94 | REAR VIEW RJ45 JACK - [23.0] - - [31.9] - 1.25 | [14.1] .55 COVER CLOSED |
| USB Port Adapters | [99] 3.9 | USB 3.0 TYPE A [32.0] [32.0] [21.26 [38.8] [8.8] [35] [21.26] | REAR VIEW USB 3.0 TYPE A [23.0] .91 .91 .25 | [14.1] 55 COVER CLOSED |

<