


YEL,PVC,3X18+12X22,S-DF,ITC,MSHA Instrumentation Tray Cable – Reelfast™ Bulk Cable



Features



- ITC 150V
- PLTC 300V
- UL/CSA AWM 300V
- CMX OUTDOOR 300V
- CMG 300V
- Instrumentation Tray Cable
- Yellow PVC jacket, shielded, 3X18+12X22 AWG
- Sunlight Resistant
- -40 Cold Bend Rating
- Oil Resistant
- Flame Ratings: UL 1685 FT4, UL1061, CSA FT4

Technical data

Type	YEL,PVC,3X18+12X22,S-DF,ITC,MSHA
ID no.	RF50625
Cable data	
Cable Platform	Instrumentation Tray Cable
Total number of conductors	15
Cable diameter	Ø 8.51 mm
Cable jacket	PVC, Yellow
Shield	Aluminum/polyester (IN)
Cable drain	22 AWG TC (Tinned Copper)
Conductor diameter	0.064 "
Conductor material	TC (tinned copper)
Conductor insulation material	SR-PVC
Conductor size	3 x 18 AWG [Similar to 0.75 mm ²]
Number of strands x O.D.	19 x 0.0092 "
Conductor diameter	0.048
Conductor insulation material	SR-PVC
Cable conductor cross-section (2)	12x 22 AWG [Similar to 0.34 mm ²]
Number of strands x O.D. (2)	19 x0.0058 mm
Conductor colors	BU, BN, GN/YL, WH, GN, GY, PK, RD, RD/BU, GY/PK, WH/GN, BN/GN, WH/YL, YL/BN, YL
Weight	0.274 lbs. /meter
Electrical properties at +20 °C	
Voltage	ITC 150V PLTC 300V

Technical data

	UL/CSA AWM 300V CMX OUTDOOR 300V CMG 300V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	17.5 Ω /1000ft max.
Mechanical and chemical properties	
Bending radius (static)	$\geq 5 \times \varnothing$
Bending radius (dynamic)	$\geq 15 \times \varnothing$
Cold bend rating	-40 °C
Ambient temperature range (static)	-40 °C...+105 °C
Ambient temperature range (dynamic)	-40 °C...+105 °C
Temperature range (installation)	-20 °C...+105 °C
Approval	
UL Approvals	UL 2250 ITC UL 13 PLTC Sunlight Resistant -40C Cold Bend Oil Res I Oil Res II UL 758 AWM 2517
CSA Approvals	CSA AWM I/II A/B UL 444 CMX OUTDOOR-CMG CSA FT4
Additional Approvals	MSHA
Compliances	RoHS CE
Note	
	- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.
	- We reserve the right to make technical alterations without prior notice.