


WHT,TPV,6X18

Washdown Cable – Reelfast™ Bulk Cable

Features



- 600V
- Washdown Cable
- White TPV jacket, 6X18 AWG
- 40 Cold Bend Rating



Technical data

Type	WHT,TPV,6X18
ID no.	RF51449
Cable data	
Cable Platform	Washdown Cable
Total number of conductors	6
Cable diameter	Ø 7.24 mm
Cable jacket	TPV, White
Conductor diameter	0.066 "
Conductor material	TC (tinned copper)
Conductor insulation material	TPC-ET
Conductor size	6 x 18 AWG [Similar to 0.75 mm²]
Number of strands x O.D.	19 x 0.0092 "
Conductor colors	GN, YL, GY, BN, BU, WH
Weight	0.183 lbs. /meter
Electrical properties at +20 °C	
Voltage	600V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	7.22 Ω/1000ft max.
Mechanical and chemical properties	
Bending radius (static)	≥ 5 x Ø
Bending radius (dynamic)	≥ 10 x Ø
Cold bend rating	-40 °C
Ambient temperature range (static)	-40 °C...+105 °C

WHT,TPV,6X18 | 05/20/2021 15-24 | technical changes reserved

Technical data

Ambient temperature range (dynamic)	-40 °C...+105 °C
Temperature range (installation)	-20 °C...+105 °C
Approval	
Compliances	RoHS
Note	
- Flex ratings may be reduced if used in extreme temperatures, exposure to certain chemicals, operating above the rated cycle speed, or operating below the rated cable bend radius.	
- We reserve the right to make technical alterations without prior notice.	