

BOARD LAYOUT

5 HOLES

4 HOLES

MALE END VIEW

DeviceNet™

SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	PA 6 NYLON/BLUE-GRAY
CONTACT MATERIAL/PLATING	BRASS/GOLD
HOUSING, LOCKNUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT [A]	4.0 A
RATED VOLTAGE [V]	30 VAC/36 VDC
NUMBER OF CONDUCTORS [AWG]	PRINTED CIRCUIT PINS
TEMPERATURE RATING	-40°C to +80°C (-40°F to +176°F)
PROTECTION CLASS	MEETS NEMA 1,3,4,6P AND IEC IP68

MAX. RECOMMENDED PANEL MOUNTING

M12X1 LOCKNUT

PCB TOP

MOUNTING HOLE

LOCKNUT NOT SHOWN

↑ = 90° CORDSET CABLE DIRECTION

NOTES:  
1.) UNIT SNAP-FITS INTO 0.062 TO 0.125 THICK PC BOARDS.  
2.) SPACER PERMANENTLY ATTACHED TO PINS FOR ALIGNMENT.

F	ADD WASHER PER ECO	KMY	04/23/14	45597
REV	DESCRIPTION	BY	DATE	ECO NO.

RELATED DOCUMENTS

3RD ANGLE PROJECTION

THIS DRAWING IS CONFIDENTIAL AND THE PROPERTY OF TURCK INC. USE OF THIS DOCUMENT WITHOUT WRITTEN PERMISSION IS PROHIBITED.

TURCK INC

High Technology Sensors and Automation Controls

3000 CAMPUS DRIVE  
MINNEAPOLIS, MN 55441  
1-800-544-7769  
(763) 553-7300  
(763) 553-0708 fax  
turck.com

MATERIAL

FINISH

DRFT IK

APVD

UNIT OF MEASUREMENT  
MILLIMETER [ INCH ]

DO NOT SCALE THIS DRAWING

DATE 07/26/00

SCALE 2=1.0

DESCRIPTION  
WFS 57-PCB/C1101

IDENTIFICATION NO.  
U2369-101

REV  
F