




The module rack MT08-N consists of a back-plane and the actual rack system. It can accommodate 2 gateways, 2 power supply units as well as 8 I/O modules. Up to 64 binary inputs/outputs or 32 analog inputs/outputs resp. a mix of both can be connected to it.

All modules can be plugged and unplugged under power without interrupting the data transmission. The same applies to redundant gateways and power supply modules.


The module rack can only be used in non-Ex areas for non-Ex signals.

The rack system is made of continuously cast aluminum. This ensures increased stability and shielding. The module rack is suited for switch cabinet and rack mounting.

- **Module rack for max. 8 I/O modules, 2 gateways and 2 power supply modules**
- **The terminals for the signal connection level are available as accessories**

Type designation	MT08-N
Ident-No.	9100689
Slots	
DC power supply	2
Gateway	2
Block I/O	8
Terminal cross-section	1.5 mm ²
Bus connection	2 x 9-pin SUB-D
Bus address	2 x decimal-coded rotary switches
Housing material	Aluminium, extrusion profile
Connection mode	Mounting panel
Protection class	IP20
Ambient temperature	-20...+70 °C
Relative humidity	≤ 93 % at 40 °C acc. to EN 60068-2-78: test cab
Vibration test	acc. to IEC 60068-2-6
Shock test	acc. to IEC 60068-2-27
EMC	acc. EN 61326-1 (2013)
	acc. to Namur NE21 (2012)
Dimensions	235 x 260 x 130 mm

Dimensions



Accessories

Type code	Ident-No.	Description	Dimension drawing
STB16-4RS/1.5-BK	9909624	16-pcs. set: 4-pin terminal block, screw clamps black	
STB16-4RC/1.5-BK	9909625	16-pcs. set: 4-pin terminal block, cage clamps black	