


IP-Link Optical Fiber

PUR Cable Jacket

SFOL- 0.2M



- POF optical fiber for IP-Link
- Fiber core PMMA 980 µm
- Fiber insulation PE 2.2 mm
- PUR jacket, 5.5 mm
- Muting (650 nm) < 190 dB/km
- Muting (660 nm) < 290 dB/km
- Numeric aperture 0.5
- Qualified for drag chain use
- Flame-retardant
- Halogen-free acc. to IEC60754
- Excellent resistance to oil, grease, acids and alkaline solutions
- Cable length: 0.2 m

Type designation		SFOL- 0.2M
Ident-No.		6603379
Cable diameter		5.5mm
Cable length (L)		0.2
Cable jacket		PUR, Orange
Bending radius (trailing application)		Ø 55mm, ≥2Mil. cycles
Ambient temperature		
Qualified for drag chain use		yes
Oil-resistant		yes
Halogen-free		yes

Functional principle

The photoelectric sensor for IP-Link is a pre-moulded polymer optical fiber (POF) for the modular fieldbus I/O system piconet.

The possibilities for industrial application range from static installations in cable ducts, pipes and racks up to dynamic installations such as dragchains.

The preassembled IP-Link fiber-optic cable together with the IP-Link socket of the piconet coupling and extension modules are a qualified IP67, shock and vibration tested combination.