


# FOUNDATION™ fieldbus and PROFIBUS-PA IP20 junction box, 4-channel JRBS-40-4C/EX



The 4-channel Ex junction box JRBS-40-4C/EX is designed for fieldbus systems according to IEC 61158-2, i.e. it is suited for both FOUNDATION™ fieldbus as well as PROFIBUS-PA.

The housing is made of powder-coated aluminium and is IP20 rated.

The junction box is equipped with an activatable terminating resistor for the bus. The switch is integrated in the housing on the board.

Shielding and housing can be connected directly via a second switch which is also located on the board.

**Note:** It must be ensured that there is sufficient equipotential bonding in the system. The device is connected to the equipotential bonding via the housing's M5 x 1 grounding bolt.

**Accessories:** To increase the degree of protection, there are various aluminium and stainless steel housings with IP6x rating and various cable glands available on request.

- Entity and FISCO compliant according to IEC 60079-11
- Junction box for DIN rail mounting
- Switch-in terminating resistor
- Cable shielding: Capacitive or direct connection with housing potential selectable via switch
- aluminium housing


# FOUNDATION™ fieldbus and PROFIBUS-PA

## IP20 junction box, 4-channel

### JRBS-40-4C/EX

<b>Type designation</b>	JRBS-40-4C/EX
Ident-No.	6611448
<b>Fieldbus standard</b>	IEC 61158-2
<b>Operating voltage range</b>	9...32 VDC
<b>Ex approval acc. to conformity certificate</b>	PTB 05 ATEX 2002
Device designation	Ex II 2 G Ex ib IIC/IIB T4
Device marking	Ex II 2(1) G Ex ia IIC/IIB T4 Ex II 2 G (2D) Ex ib [ibD] IIB T4 Ex II 2(1) G (1D) Ex ia [iaD] IIB T4 FISCO / Entity field device
Entity Parameter	
Max. output voltage $U_o$	$\leq 24 \text{ V}$
Max. output current $I_o$	$\leq 250 \text{ mA}$
Max. output power $P_o$	$\leq 2560 \text{ mW}$
Max. input voltage $U_i$	$\leq 24 \text{ V}$
Max. input current $I_i$	$\leq 250 \text{ mA}$
Max. input power $P_i$	$\leq 2560 \text{ mW}$
FISCO parameter according to IEC 60079-11	
Max. output voltage $U_o$	$\leq 17.5 \text{ V}$
Max. output current $I_o$	$\leq 380 \text{ mA}$
Max. output power $P_o$	$\leq 5320 \text{ mW}$
Max. input voltage $U_i$	$\leq 17.5 \text{ V}$
Max. input current $I_i$	$\leq 380 \text{ mA}$
Max. input power $P_i$	$\leq 5320 \text{ mW}$
External inductance/capacitance L/C,	Trunk (In/Out): negligible / $\leq 5.00 \text{ nF}$ per field current circuit: negligible / $\leq 0.82 \text{ nF}$ $\Sigma$ field current circuits: negligible / $\leq 5.00 \text{ nF}$
Ex approval acc. to conformity certificate	TURCK Ex-13002H X
Device designation	Ex II 3 G Ex nA IIC T4 Gc
Device designation	Ex II 3 G Ex ic IIC T4 Gc
<b>Electrical connection</b>	Spring type terminals
Segment IN	4 x Cage clamp terminal
Segment OUT	1 x Cage clamp terminal
Spur line	1 x Cage clamp terminal
Terminal cross-section	0.2...2.5 mm <sup>2</sup> (24 ... 13 AWG)
Earthing bolt	M5 x 1
<b>Protection class</b>	IP20
MTTF	705 years acc. to SN 29500 (Ed. 99) 40 °C
Ambient temperature	-25...+70 °C
Housing material	Aluminium
Housing color	Black
Dimensions	107 x 31 x 75.5 mm
Connection mode	snap-fit on DIN rail (DIN 60715)

#### Dimensions



#### Terminal assignment

