

Eaton XT IEC contactor

XTCE250L22TD

Dimensions:

- **Height:** 7.08661417 IN
- **Length:** 8.18897638 IN
- **Width:** 5.51181102 IN

Weight: .61729433 LB

Notes: Screw terminals (6-65A); 5 mm (80-150A);
no lugs (185-2000A)

Warranties: No Data

Specifications:

- **Amperage Rating:** 250A
- **Coil Voltage:** 24-48 Vdc
- **Contact Configuration:** 2NO-2NC
- **Max Hp Rating:** 75, 100, 200, 250 hp (3PH
@200,230,460,575 V)
- **Number Of Poles:** Three-pole
- **Operation:** Non-reversing
- **Series:** XT IEC series
- **Terminals:** Screw terminals
- **Type:** Full voltage non-reversing contactor

Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [XTCE_L 3D Inventor](#)
- [XTCE_L AutoCAD 2D Footprint](#)
- [XTCE_L AutoCAD 2D Footprint \(mm\)](#)
- [XTCE_L 3D Model Xchange](#)
- [XTCE_L 2D Drawing Xchange](#)
- [XTCE_L 2D PDF](#)
- [Global Data Sheet - XTCE250L22TD](#)
- [Voltage Sag Ride Through for XT IEC
Contactor Frames L - N](#)

Certifications:

- UL Listed
- CSA Certified

- IEC 60947
- EN 60947

Product compliance:

- CE Marked
- RoHS Compliant

© 2016 Eaton. All rights reserved.