

Product data sheet

Characteristics

15S40FSS

TRANSFORMER DRY 1PH 15KVA

480V-120/240V

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 7,036.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary to Secondary Voltage	480 V 120/240 V
Full Capacity Taps	2 5 % FCBN

Complementary

Enclosure Code	15B
Phase	1 phase
Power Rating	15 kVA
Temperature rise	115 °C
Height	20 in (508.00 mm)
Width	15 in (381.00 mm)
Depth	13.5 in (342.90 mm)
Enclosure mounting	Wall mounted
Net Weight	225 lb(US) (102.06 kg) 225.00 lb(US) (102.06 kg)
Enclosure material	Stainless Steel

Environment

Enclosure Type	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	CULus CSA UL Listed

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
GTIN	00785901538301
Nbr. of units in pkg.	1
Package weight(Lbs)	320.00 lb(US) (145.15 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	13.75 in (34.925 cm)
Package 1 width	15.00 in (38.1 cm)
Package 1 Length	19.00 in (48.26 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------