Product data sheet Characteristics

HGN36125

Circuit breaker, PowerPacT H, thermal magnetic, unit mount, 125A, 3 pole, 18 kA, 600 VAC, 80% rated







Main

Range of product	PowerPact H
Product or component type	Circuit breaker

Complementary

Complementary		
Line Rated Current	125 A	
Number of Poles	3P	,
Breaking capacity code	G	
Mounting mode	Plug-in	
Magnetic hold current	900 A	
Magnetic tripping current	1700 A	
Electrical connection	Plug-in line Plug-in load	
Height	6.4 in (162.56 mm)	<u> </u>
Width	4.12 in (104.65 mm)	<u>.</u> 3
Depth	12.08 in (306.83 mm)	
Continuous current rating	80 %	11.0

Environment

Product certifications	CSA IEC
	CE
	UL Listed
	CCC
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01115-HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901634607
Package weight(Lbs)	5.00 lb(US) (2.268 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
PVC free	Yes	

Contractual warranty

Contractadi Warranty	
Warranty	18 months