



Main

Range	Multi 9
Product name	Multi 9 C60
Product or component type	Miniature circuit-breaker
Device short name	C60N
Device application	Distribution
Poles description	2P
Number of protected poles	2
Line Rated Current	50 A 122 °F (50 °C) EN/IEC 60947-2
Network type	DC AC
Trip unit technology	Thermal-magnetic
Curve code	D
Breaking capacity	20 kA Icu <= 125 V DC EN/IEC 60947-2 10 kA Icu 415 V AC 50/60 Hz between phases EN/IEC 60947-2 20 kA Icu 240 V AC 50/60 Hz between phases EN/IEC 60947-2 6 kA Icu 440 V AC 50/60 Hz between phases EN/IEC 60947-2
Utilisation category	Category A EN/IEC 60947-2
Suitability for isolation	Yes EN/IEC 60947-2
Standards	EN/IEC 60947-2
Product certifications	EAC KC

Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	240 V AC 50/60 Hz between phases 415 V AC 50/60 Hz between phases 440 V AC 50/60 Hz between phases <= 125 V DC
Magnetic tripping limit	12 x In +/- 20 % AC 17 x In +/- 20 % DC
[Ics] rated service breaking capacity	7.5 kA 75 % EN/IEC 60947-2 - 415 V AC 50/60 Hz 16 kA 75 % EN/IEC 60947-2 - 240 V AC 50/60 Hz 4.5 kA 75 % EN/IEC 60947-2 - 440 V AC 50/60 Hz 20 kA 100 % EN/IEC 60947-2 - <= 125 V DC

[Ui] rated insulation voltage	500 V AC 50/60 Hz EN/IEC 60947-2
[Uimp] rated impulse withstand voltage	6 kVEN/IEC 60947-2
Contact position indicator	Yes
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	4
Height	3.19 in (81 mm)
Width	1.42 in (36 mm)
Depth	2.83 in (72 mm)
Net Weight	0.53 lb(US) (0.24 kg)
Color	Gray
Mechanical durability	20000 cycles
Electrical durability	10000 cycles
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminal top or bottom) 0.00...0.05 in ² (1.5...35 mm ²) - rigid Tunnel type terminal top or bottom) 0.00...0.05 in ² (1.5...35 mm ²) - flexible Tunnel type terminal top or bottom) 0.00...0.05 in ² (1.5...35 mm ²) - flexible with ferrule
Wire stripping length	0.55 in (14 mm) top or bottom
Tightening torque	30.98 lbf.in (3.5 N.m) top or bottom
Earth-leakage protection	Separate block

Environment

Heat dissipation	9.6 W 415 V - 50 A
IP degree of protection	IP20IEC 60529 IP40 modular enclosure)IEC 60529
Pollution degree	3 EN/IEC 60947-2
Overvoltage category	IV
Tropicalisation	2 IEC 60068-1
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	-22...158 °F (-30...70 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)

Ordering and shipping details

GTIN	03606480929274
Package weight(Lbs)	0.54 lb(US) (0.245 kg)

Packing Units

Package 1 Height	0.750 dm
Package 1 width	0.360 dm
Package 1 Length	0.850 dm