

DTU225

Safety switch, double throw, non fusible, 400A,
240 VAC/250 VDC, 2 poles, 50 hp, NEMA 1

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 5,850.00 USD



Main

Product	Double Throw Safety Switch
Duty Rating	General duty
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Number of Poles	2
Current Rating	400 A
Voltage Rating	240 V AC 250 V DC
Enclosure Rating	NEMA 1
Maximum Horse Power Rating	50 hp 250 V at DC

Complementary

Short-circuit current	10 kA H or K
Fuse type	H or K
Mounting Type	Surface
Wire Size	AWG 1/0...750 kcmil aluminium/copper
Depth	7.25 in (184.15 mm)
Width	24 in (609.60 mm)
Height	54.20 in (1376.68 mm)
Net Weight	130.07 lb(US) (59 kg)

Environment

Certifications	UL Listed
----------------	-----------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	03606481716750
Nbr. of units in pkg.	1
Package weight(Lbs)	130.00 lb(US) (58.967 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	54.21 in (137.7 cm)
Package 1 width	24.02 in (61 cm)
Package 1 Length	7.24 in (18.4 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile