

Product data sheet

Characteristics

DTU465

Safety switch, double throw, non fusible, 400A,
600 VAC/VDC, 4 poles, 350 hp, NEMA 1

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 13,321.00 USD



Main

Product	Double Throw Safety Switch
Duty Rating	General duty
Disconnect Type	Non-fusible disconnect switch
Factory Installed Neutral	None
Number of Poles	4
Current Rating	400 A
Voltage Rating	600 V AC 600 V DC
Enclosure Rating	NEMA 1
Maximum Horse Power Rating	125 hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 250 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 350 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 50 hp 250 V at DC

Complementary

Short-circuit current	10 kA H or K 100 kA R, J or T
Fuse type	H or K R, J or T
Mounting Type	Surface
Wire Size	AWG 1/0...750 kcmil aluminium/copper
Tightening torque	550 lbf.in (62.14 N.m) 0.08...0.47 in ² (53.49...304 mm ²) (AWG 1/0...750 kcmil) 62.14 lbf.in (7.02 N.m) 0.08...0.24 in ² (53.49...152 mm ²) (2 x AWG 1/0...2 x 300 kcmil)
Depth	8.88 in (225.55 mm)
Width	28.40 in (721.36 mm)
Height	64.20 in (1630.68 mm)
Net Weight	220.46 lb(US) (100 kg)

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Environment

Certifications	UL Listed
----------------	-----------

Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	03606481716798
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US