Product data sheet Characteristics


25S7F TRANSFORMER DRY 1PH 25KVA 208V-120/240V

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 7,591.00 USD



Main

Product or component type	Dry Sealed Transformer
Primary to Secondary Voltage	208 V 120/240 V
Full Capacity Taps	0

Complementary

Enclosure Code	15B	
Phase	1 phase	
Power Rating	25 kVA	:
Temperature rise	115 °C	
Height	20 in (508.00 mm)	
Width	15 in (381.00 mm)	
Depth	13.5 in (342.90 mm)	
Enclosure mounting	Wall mounted	
Enclosure material	Painted sheet steel	

Environment

Enclosure Type	NEMA 3R	0 0
Insulation temperature	356 °F (180 °C)	
Product certifications	CULus UL Listed CSA	n is not inte

Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Nbr. of units in pkg.	1
Package weight(Lbs)	385 lb(US) (174.63 kg)
Returnability	No
Packing Units	
Package 1 Height	13.75 in (34.925 cm)
Package 1 width	15.00 in (38.100 cm)
Package 1 Length	19.00 in (48.260 cm)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Contractual warranty		
Warranty	18 months	