

BDA36125

PowerPact B Circuit Breaker, 125A, 3P,
600Y/347V AC, 14kA at 600Y/347 UL, I-Line

Product availability : Stock - Normally stocked in distribution facility



Price* : 1,837.00 USD



Main

| | |
|---------------------------|-----------------|
| Range | PowerPact |
| Product name | PowerPact B |
| Device short name | BD 125 |
| Product or component type | Circuit breaker |
| Device application | Distribution |

Complementary

| | |
|--|---|
| Line Rated Current | 125 A |
| Number of Poles | 3P |
| Control type | Toggle |
| Breaking capacity code | D |
| Breaking capacity | 25 kA 208Y/120 V AC 50/60 Hz UL 489 25 kA 240 V AC 50/60 Hz UL 489 18 kA 480/277 V AC 50/60 Hz UL 489 18 kA 480 V AC 50/60 Hz UL 489 14 kA 600Y/347 V AC 50/60 Hz UL 489 10 kA 250 V DC UL 489 |
| [Ue] rated operational voltage | 525 V AC 50/60 Hz UL 489 |
| [Ics] rated service breaking capacity | 25 kA 220...240 V AC 50/60 Hz IEC 60947-2 14 kA 500...525 V AC 50/60 Hz IEC 60947-2 18 kA 380...415 V AC 50/60 Hz IEC 60947-2 18 kA 440 V AC 50/60 Hz IEC 60947-2 |
| [Uimp] rated impulse withstand voltage | 8 kV IEC 60947-2 |
| Trip unit technology | Thermal-magnetic |
| Continuous current rating | 80 % |
| [Ui] rated insulation voltage | 800 V IEC 60947-2 |
| Suitability for isolation | Yes conforming to IEC 60947-2 |

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|-----------------------------|--|
| Utilisation category | Category A |
| Mechanical durability | 20000 cycles IEC 947-1 Annex K ed 5.2 |
| Electrical durability | 10000 cycles IEC 947-1 Annex K ed 5.2 440 V In |
| Connection pitch | 1.06 in (27 mm) |
| AWG gauge | AWG 14...AWG 2/0 aluminium/copper |
| Local signalling | for presence of auxiliary contacts flag (green) |
| Mounting mode | I-Line |
| Electrical connection | I-Line connection line Lugs load |
| Mounting height | 4.49 in (114 mm) |
| Tightening torque | 31.86...38.94 lbf.in (3.6...4.4 N.m) 0.00...0.01 in ² (2.5...6 mm ²) (AWG 14...AWG 10) 44.25...54.87 lbf.in (5...6.2 N.m) 0.02...0.11 in ² (10...70 mm ²) (AWG 8...AWG 2/0) |
| Number of slots | 1 auxiliary switch OF plug-in 1 voltage release MN or MX plug-in 1 alarm switch SD plug-in |
| Power wire stripping length | 0.79 in (20 mm) |
| Color | Grey (RAL 7016) |
| 9 mm pitches | 9 |
| Height | 5.39 in (137 mm) |
| Width | 3.19 in (81 mm) |
| Depth | 3.50 in (89 mm) |
| Net Weight | 2.90 lb(US) (1.315 kg) |
| Quantity per set | Set of 1 |
| Phase connection | ABC |

Environment

| | |
|---------------------------------------|---|
| Quality labels | CE |
| Standards | GB 14048.2 EN/IEC 60947-5-1 NMX J-266 NEMA AB1 UL 489 EN/IEC 60947-2 CSA C22.2 No 5 |
| Product certifications | UL IEC CCC EAC CSA NOM |
| IP degree of protection | Front cover IP40 IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 62262 |
| Pollution degree | 3 conforming to IEC 60947-1 |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -58...185 °F (-50...85 °C) |
| Operating altitude | < 6561.68 ft (2000 m) without derating 5000 m with derating |

Ordering and shipping details

| | |
|-----------------------|----------------------------|
| Category | 01133 - BDA I-LINE BREAKER |
| Discount Schedule | DE2 |
| GTIN | 03606481152763 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 4.21 lb(US) (1.91 kg) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 4.88 in (12.4 cm) |
| Package 1 width | 8.11 in (20.6 cm) |
| Package 1 Length | 12.80 in (32.5 cm) |

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| RECh Regulation | RECh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| PVC free | Yes |
| Halogen content performance | Halogen free product |