

Product data sheet

Characteristics

QOU2353100

Mini circuit breaker, QOU, 35A, 2 pole, 120/240 VAC, 10kA, mounting foot



Price* : 105.00 USD



Main

Product or component type	Miniature circuit-breaker
Range of product	QOU
Circuit breaker type	Standard
Circuit breaker application	HACR and Switching Duty rated

Complementary

Line Rated Current	35 A
Electrical connection	Slotted box lugs, line side Slotted box lugs, load side
[Ue] rated operational voltage	120/240 V AC 120 V AC 48 V DC
Mounting mode	Unit mount
AWG gauge	AWG 14...AWG 2 aluminium/copper
Height	4.05 in (102.87 mm)
Width	1.5 in (38.10 mm)
Depth	2.95 in (74.93 mm)
Tightening torque	45 lbf.in (5.08 N.m) (AWG 14...AWG 2)

Environment

Product certifications	UL Listed IEC CSA
------------------------	-------------------------

Ordering and shipping details

Category	00900-QOU BREAKERS & SWITCH
----------	-----------------------------

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Jul 30, 2021

Discount Schedule	DE2
GTIN	00785901696100
Nbr. of units in pkg.	1
Package weight(Lbs)	16.96 oz (480.808 g)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.70 in (9.398 cm)
Package 1 width	4.90 in (12.446 cm)
Package 1 Length	2.20 in (5.588 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Halogen content performance	Halogen free product

Contractual warranty

Warranty	18 months
----------	-----------

Technical drawings of the 40C sensor showing top and side views with dimensions in inches and millimeters.

Top View Dimensions:

- Overall Width: 2.95 [75]
- Overall Height: 5.00 [127]
- Left Side Flange Width: 1.15 [29]
- Left Side Flange Thickness: .38 [10]
- Right Side Flange Width: .35 [9]
- Right Side Flange Thickness: .18 [5]
- Top Mounting Hole Spacing: 2.03 [51]
- Top Mounting Hole Diameter: .13 [3]
- Top Mounting Hole Position from Left Edge: .25 [6]
- Top Mounting Hole Position from Right Edge: .24 [6]
- Top Mounting Hole Position from Bottom Edge: .61 [16]
- Top Mounting Hole Position from Right Edge: .26 [7]
- Top Mounting Hole Position from Bottom Edge: 1.37 [35]
- Top Mounting Hole Position from Right Edge: .36 [9]
- Top Mounting Hole Position from Bottom Edge: .63 [16]
- Top Mounting Hole Position from Right Edge: .68 [17]

Side View Dimensions:

- Overall Width: 2.95 [75]
- Overall Height: 5.00 [127]
- Left Side Flange Width: 1.15 [29]
- Left Side Flange Thickness: .38 [10]
- Right Side Flange Width: .35 [9]
- Right Side Flange Thickness: .18 [5]
- Top Mounting Hole Spacing: 2.03 [51]
- Top Mounting Hole Diameter: .13 [3]
- Top Mounting Hole Position from Left Edge: .25 [6]
- Top Mounting Hole Position from Right Edge: .24 [6]
- Top Mounting Hole Position from Bottom Edge: .61 [16]
- Top Mounting Hole Position from Right Edge: .26 [7]
- Top Mounting Hole Position from Bottom Edge: 1.37 [35]
- Top Mounting Hole Position from Right Edge: .36 [9]
- Top Mounting Hole Position from Bottom Edge: .63 [16]
- Top Mounting Hole Position from Right Edge: .68 [17]

Mounting Options:

- FOR SURFACE MOUNT
- FOR FLUSH MOUNT

[DIMENSIONAL EXAMPLE ONLY BELOW]

