



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual
--------------------	-------------

Physical

Cable length	6 ft (1.83 m)
Color	White
Depth	9.72 in (24.7 cm)
Height	1.18 in (3 cm)
Net Weight	1.32 lb(US) (0.6 kg)
Width	3.03 in (7.7 cm)

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Plug standard	NEMA 5-15P
Maximum Input Current per phase	15 A
Switching current capacity	15 A
Nominal Input Voltage	120 V

Output

Number of power socket outlets	8
Outlet standard	NEMA 5-15R

Conformance

Product certifications	MET Canada MET USA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % Non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	56 kA common mode 28 kA normal mode
Surge energy rating	2160 J

Ordering and shipping details

GTIN	00731304336167
Package weight(Lbs)	1.54 lb(US) (0.7 kg)

Packing Units

Package 1 Height	1.89 in (4.8 cm)
Package 1 width	5.71 in (14.5 cm)
Package 1 Length	11.22 in (28.5 cm)
SCC14	10731304336164
Number of Units in Package 2	6
Package 2 Weight	10.08 lb(US) (4.57 kg)
Package 2 Height	12.6 in (320.04 mm)
Package 2 width	6.3 in (160.02 mm)
Package 2 Length	11.81 in (299.97 mm)
Number of Units in Package 3	432

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Lifetime
----------	----------