

Product data sheet

Characteristics

HJN36030M71

Motor circuit protector, PowerPacT H, 30A, 3 pole, 25 kA, 600 VAC, 80% rated



Main

Range of product	PowerPact H
Product or component type	Motor Circuit Protector

Complementary

Line Rated Current	30 A
Number of Poles	3P
Breaking capacity code	J
Mounting mode	Plug-in
Magnetic hold current	9 A
Magnetic tripping current	325 A
Electrical connection	Plug-in line Plug-in load
Height	6.4 in (162.56 mm)
Width	4.12 in (104.65 mm)
Depth	12.08 in (306.83 mm)
Continuous current rating	80 %

Environment

Product certifications	CE CSA IEC CCC UL Listed
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	01125-HJ, JJ UNT MNT MTR CIRCUIT PROTECTR
----------	---

Discount Schedule	DE2
Package weight(Lbs)	5.00 lb(US) (2.268 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes