Product data sheet Characteristics

HJN36050

Circuit breaker, PowerPacT H, thermal magnetic, unit mount, 50A, 3 pole, 25 kA, 600 VAC, 80% rated

Product availability: Non-Stock - Not normally stocked in distribution facility







Main

Range of product	PowerPact H	
Product or component type	Circuit breaker	4

Complementary

Complementary		
Line Rated Current	50 A	
Number of Poles	3P	
Breaking capacity code	J	
Mounting mode	Plug-in	
Magnetic hold current	400 A	-
Magnetic tripping current	850 A	
Electrical connection	Plug-in line Plug-in load	
Height	6.4 in (162.56 mm)	
Width	4.12 in (104.65 mm)	
Depth	12.08 in (306.83 mm)	
Continuous current rating	80 %	

Environment

ZIII OI III OI II		
Product certifications	CSA UL Listed	<u></u>
Ambient air temperature for operation	104 °F (40 °C)	. <u>.</u>

Ordering and shipping details

Category 01115 - HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH	
---	--

Discount Schedule	DE2
Nbr. of units in pkg.	1
Package weight(Lbs)	5 lb(US) (2.27 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
PVC free	Yes	

Contractual warranty

Warranty	18 months	