## Product data sheet Characteristics

# PJL36040CU44A MOLDED CASE CIRCUIT BREAKER 600V 400A

SQUARE 1





#### Main

Device short name	A
Product or component type	Circuit breaker

#### Complementary

		Y
Line Rated Current	400 A	‡ *
Number of Poles	3P	i.i.
Breaking capacity code	J	<u></u>
Electrical connection	Lugs load Lugs line	de Filide
Tightening torque	442.54 lbf.in (50 N.m) 0.150.37 in² (95240 mm²) (AWG 3/0500 kcmil) 8.8511.51 lbf.in (1.01.3 N.m)	ini o si
Height	12.86 in (326.64 mm)	eter E
Width	8.27 in (210.06 mm)	for d
Depth	8.05 in (204.47 mm)	9
Continuous current rating	100 %	

#### Ordering and shipping details

Category	01215-PG,H,J,K,L,N UNIT MT BREAKERS	•
Discount Schedule	DE2	
Package weight(Lbs)	32.00 lb(US) (14.515 kg)	
Returnability	Yes	
Country of origin	US	

#### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

### Contractual warranty

Warranty	18 months
•	