Product data sheet **Characteristics** 

# HL1IMA12C1 Surge protection device, Surgelogic, HL, 120kA, 120/240 VAC, 1 phase, 3 wire, SPD type 1

Product availability : Stock - Normally stocked in distribution facility

SQUARE D

Price\* : 9,518.00 USD



#### Main

Product	Surge protection device	
Range	Surgelogic	
Device Short Name	IMA	
Туре	HL	

### Complementary

Main		
Product	Surge protection device	
Range	Surgelogic	
Device Short Name	IMA	
Туре	HL	
Complementary		
Surge Current	120 kA	
Voltage Rating	120/240 V AC	
Number of Phases	1 phase	
Wiring Configuration	3-wire	
Connection	I-Line line Lugs ground AWG 6 copper 35.40 lbf.in (4 N.m) Lugs neutral AWG 6 copper 35.40 lbf.in (4 N.m)	
MCOV	150 V	
Max Number of Poles	3	
Rated Current	60 A	
Breaking Capacity	50 kA	
Trip Unit Technology	Thermal-magnetic	
SCCR	200 kA	
Local Signalling	Status LED green per phase normal operation Status LED red per phase fault	
Provided Equipment	Alarm enable/disable switch Surge counter Circuit breaker	
Mounting Support	Panel mounting	
Height	12.16 in (308.9 mm)	



Width	13.46 in (341.9 mm)	
Depth	5.59 in (142.1 mm)	
Cable length	19.02 in (483 mm)	

## Environment

Enclosure Rating	NEMA 1
Standards	UL 1449:ed. 3 CSA C22.2 No 8:1986 UL 96A:ed. 12 UL 489:ed. 11 CSA C22.2 No 5-09

## Ordering and shipping details

08460 - SURGE PROTECTION I-LINE
DE1B
00785901068723
10
22.14 lb(US) (10.04 kg)
Yes
MX

Offer Sustainability
----------------------

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.