# Product data sheet Characteristics

# PJM36120U44A MOLDED CASE CIRCUIT BREAKER 600V 1200A







#### Main

Device short name	A
Product or component type	Circuit breaker

### Complementary

o o mpio montary		
Line Rated Current	1200 A	<u></u>
Number of Poles	3P	
Breaking capacity code	J	
Electrical connection	Lugs load Terminal nut line	
Tightening torque	442.54 lbf.in (50 N.m) 0.150.37 in² (95240 mm²) (AWG 3/0500 kcmil) 8.8511.51 lbf.in (1.01.3 N.m)	i.m.
Height	16.16 in (410.46 mm)	
Width	8.27 in (210.06 mm)	ğ
Depth	8.05 in (204.47 mm)	<u> </u>
Continuous current rating	80 %	. <u>.</u>

#### Ordering and shipping details

Category	01215-PG,H,J,K,L,N UNIT MT BREAKERS	
Discount Schedule	DE2	
Package weight(Lbs)	32.00 lb(US) (14.515 kg)	
Returnability	Yes	
Country of origin	US	

#### Offer Sustainability

one outside the		
Sustainable offer status	Green Premium product	

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
PVC free	Yes	

## Contractual warranty

Warranty	18 months