Product data sheet Characteristics

EX500T211H

DOE 2016 LV XFMR, 3 Phase, 500kVA, 208 Delta-208Y/120, AL, 150°C Rise-220C INS

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 31,050.00 USD



Main

Range of product	Square D
Product or component type	DOE 2016 energy efficient transformer
Device short name	DOE 2016
Transformer type	Energy efficient
Device application	Low voltage electrical distribution

Complementary

Main Range of product Square D Doublet to severe officient transformers	
Range of product Square D	
DOE 2010 and any officiant transformer	
Product or component type DOE 2016 energy efficient transformer	
Device short name DOE 2016	
Transformer type Energy efficient	
Device application Low voltage electrical distribution	
Complementary	
Phase 3 phase	
Rated operational power in VA 500 kVA	
Network frequency 60 Hz	
Type of cooling Natural convection	
Primary voltage 208 V delta	
Number of tap-offs 1 5 % FCAN 2 5 % FCBN	
Secondary voltage 208Y/120 V	
Coil Material Aluminium	
Basic IMP level (BIL) 10 kV	
Temperature Rise 150 °C 220 °C insulated	
DOE Efficiency 99.24 % at 35 % load factor , 167 °F (75.0 °C)
Sound Level 6 dB NEMA ST-20 56 dB	
Height 70.98 in (1803 mm)	
Depth 37.91 in (963 mm)	
Width 48.27 in (1226 mm)	
Net Weight 2915.00 lb(US) (1322.22 kg)	
* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.	ce.

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Mounting support	Floor Floor, with 7400FMB
Degree of protection	UL type 1 UL type 2, with 7400DS30J UL type 3R, with 7400WS30J

Environment

Ambient air temperature for operation	104 °F (40 °C)
Average ambient air temperature for operation	30 °C
Standards	UL 1561 CSA C22.2 No 47 NEMA ST-20

Ordering and shipping details

Category	16502 - EX MTO 500 & ABOVE SPECIAL VOLTAGE
Discount Schedule	PE2X
Nbr. of units in pkg.	1
Package weight(Lbs)	3260 lb(US) (1478.71 kg)
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product