

# Product data sheet

## Characteristics

# 8910DPA23V09Y125Y239

Contactor, Definite Purpose, 25A, 3 pole, 20 HP at 575 VAC, 3 phase, 208/240 VAC 60 Hz 220 VAC 50 Hz coil, open

Product availability : Non-Stock - Not normally stocked in distribution facility



Price\* : 102.00 USD



### Main

Product or component type	Definite Purpose Contactor
Line Rated Current	25 A
Number of Poles	3P
Pole contact composition	3 NO
Range of product	DPA

### Complementary

Maximum Horse Power Rating	2 hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase 10 hp 230 V AC, 3 phase 15 hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase
Locked rotor rated current	125 A 460 V AC 100 A 575 V AC 150 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	208...240 V AC 60 Hz 220 V AC 50 Hz
Phase	3 phase
Electrical connection	Box lugs Screw terminal

### Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Ordering and shipping details

Category	21342 - 8910 DPA 2_(25 AMP)
Discount Schedule	CP1B
GTIN	00785901511229
Nbr. of units in pkg.	1
Package weight(Lbs)	1.02 lb(US) (0.46 kg)
Returnability	No
Country of origin	CN

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.