Product data sheet Characteristics

EX500T79H

DOE 2016 LV XFMR, 3 Phase, 500kVA, 600 Delta-208Y/120, AL, 150°C Rise-220C INS

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 31,050.00 USD



Main

Range of product	Square D
Product or component type	DOE 2016 energy efficient transformer
Device short name	DOE 2016
Transformer type	Energy efficient
Device application	Low voltage electrical distribution

Complementary

THE		
MINIMA MARKATANA		
Main		
Range of product	Square D	
Product or component type	DOE 2016 energy efficient transformer	
Device short name	DOE 2016	
Transformer type	Energy efficient	
Device application	Low voltage electrical distribution	
Complementary		
Phase	3 phase	
Rated operational power in VA	500 kVA	
Network frequency	60 Hz	
Type of cooling	Natural convection	
Primary voltage	600 V delta	
Number of tap-offs	2 2.5 % FCAN 2 2.5 % FCBN	
Secondary voltage	208Y/120 V	
Coil Material	Aluminium	
Basic IMP level (BIL)	10 kV	
Temperature Rise	150 °C 220 °C insulated	
Sound Level	6 dB NEMA ST-20 56 dB	
Height	70.98 in (1803 mm)	
Depth	37.91 in (963 mm)	
Width	48.27 in (1226 mm)	
Net Weight	2915.00 lb(US) (1322.22 kg)	
Mounting support	Floor	
Price is "List Price" and may be subject to a trade	e discount – check with your local distributor or retailer for actual price.	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

	Floor, with 7400FMB
Degree of protection	UL type 1 UL type 2, with 7400DS30J UL type 3R, with 7400WS30J
Electrical connection	4 Hole Nema Pad primary 0.44 in (11.1 mm) 6 Hole Nema Pad secondary 0.44 in (11.1 mm) 8 Hole Nema Pad sec - XO 0.44 in (11.1 mm)

Environment

Ambient air temperature for operation	104 °F (40 °C)
Average ambient air temperature for operation	30 °C
Standards	UL 1561 CSA C22.2 No 47 NEMA ST-20

Ordering and shipping details

Category	16502 - EX MTO 500 & ABOVE SPECIAL VOLTAGE
Discount Schedule	PE2X
Nbr. of units in pkg.	1
Package weight(Lbs)	3260 lb(US) (1478.71 kg)
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product