

Product availability : Non-Stock - Not normally stocked in distribution facility



Price* : 45,921.00 USD



Main

Range of product	Square D
Product or component type	Harmonic Mitigating Transformer
Device application	Low voltage electrical distribution

Complementary

Phase	3 phase
Rated operational power in VA	500 kVA
Network frequency	60 Hz
Type of cooling	Natural convection
Primary voltage	480 V
Number of tap-offs	1 5 % FCAN 2 5 % FCBN
Secondary voltage	208Z/120 V
Coil Material	Copper
Basic IMP level (BIL)	10 kV
Temperature Rise	150 °C 220 °C insulated
Height	71.00 in (1803.4 mm)
Depth	37.89 in (962.51 mm)
Width	48.26 in (1225.8 mm)
Net Weight	4400.01 lb(US) (1995.81 kg)
Mounting support	Floor
Degree of protection	UL type 1 UL type 3R, with accessory

* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Ambient air temperature for operation	104 °F (40 °C)
Average ambient air temperature for operation	30 °C
Standards	UL 1561 CSA C22.2 No 47 NEMA ST-20

Ordering and shipping details

Category	16253 - 3PH EX/2016 K13 15-150KVA LVGP XFMR
Discount Schedule	PE2X
Nbr. of units in pkg.	1
Package weight(Lbs)	4000 lb(US) (1814.37 kg)
Returnability	No

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
PVC free	Yes