### Product data sheet Characteristics

# MGL36800AASA

Circuit Breaker, PowerPact M, electronic trip, unit mount, 800A, 3 pole, 18 kA, 600 VAC, aux switch, shunt trip







#### Main

Product Type	Circuit breaker	
Range	PowerPact M	
Breaking Capacity Code	G	
Trip Unit Technology	Electronic, basic, ET 1.0, LI	
Accessory Type	Auxiliary switch 24 V 1 NO + 1 NC Shunt trip 110/130 V AC	

#### Complementary

EN STATE OF		
Main		
Product Type	Circuit breaker	
Range	PowerPact M	
Breaking Capacity Code	G	
Trip Unit Technology	Electronic, basic, ET 1.0, LI	
Accessory Type	Auxiliary switch 24 V 1 NO + 1 NC Shunt trip 110/130 V AC	
Complementary		
Current Sensor Rating Range	800 A	
Rated Current	800 A	
Rated Operational Voltage	600 V AC	
Mounting Mode	Unit mount	
Poles Description	3P	
Breaking Capacity	65 kA 240 V AC 35 kA 480 V AC 18 kA 600 V AC	
Circuit Breaker Type	M-frame	
Continuous Current Rating	80 %	
Electrical Connection	Lugs load Lugs line	
Magnetic Tripping Current	16008000 A	
Terminal Identifier	AL800M23K	
AWG Gauge	AWG 3/0500 kcmil aluminium/copper)3	
Tightening Torque	442.54 lbf.in (50 N.m) 0.150.37 in² (95240 mm²) (AWG 3/0500 kcmil)	
Height	12.86 in (326.6 mm)	
Width	0.32 in (8.06 mm)	

Depth	8.27 in (210 mm)
Environment	
Certifications	CSA
	IEC
	UL Listed
Ordering and shipping details	
Category	01205-MG, MJ UNIT MOUNT BREAKER
Discount Schedule	DE2
Package weight(Lbs)	29.00 lb(US) (13.154 kg)
Returnability	No
Country of origin	US
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant
	EU RoHS Declaration
Mercury free	Yes

#### Contractual warranty

RoHS exemption information

China RoHS Regulation

Environmental Disclosure

Circularity Profile

PVC free

Yes

Yes

China RoHS declaration

End of Life Information

**Product Environmental Profile** 

Contractual warranty		
Warranty	18 months	

Product out of China RoHS scope. Substance declaration for your information.

# MGL36800AASA

### **Approximate Dimensions**

