Product data sheet Characteristics

HLA36060U33X

Circuit breaker, PowerPacT H, Micrologic 3.2S, I-Line, 60A, 3 pole, 50 kA, 600 VAC, phase ABC, 80% rated



Price*: 3,370.00 USD



Main

Range of product	PowerPact H	٥
Product or component type	Circuit breaker	- the

Complementary

Complementary		;
Line Rated Current	60 A	<u> </u>
Number of Poles	3P	
Breaking capacity code	L	 .c. .c.
Mounting mode	I-Line	<u> </u>
Electrical connection	I-Line connection line Lugs load	of for de
Tightening torque	44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) (AWG 14AWG 3/0)	<u>v</u>
Phase connection	ABC	t
Height	9.73 in (247.14 mm)	. <u></u> . <u>v</u>
Width	4.48 in (113.79 mm)	
Depth	4.36 in (110.74 mm)	at it
Continuous current rating	80 %	

Environment

Product certifications	UL Listed IEC
	CE CCC
	CSA
Ambient air temperature for operation	104 °F (40 °C)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	01104-H/J ELEC TRIP I-LINE BREAKER / SW
Discount Schedule	DE2
Package weight(Lbs)	8.00 lb(US) (3.629 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes

Contractual warranty

Contraction Warranty	
Warranty	18 months