Product data sheet Characteristics

HLF36040

Circuit breaker, PowerPacT H, thermal magnetic, unit mount, 40A, 3 pole, 50 kA, 600 VAC, 80% rated

Product availability: Non-Stock - Not normally stocked in distribution facility





Price*: 4,273.50 USD



Main

PowerPact H	
40 A	
3P	
L	
Unit mount	
400 A	
850 A	
Busbar connection line Busbar connection load	
44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) (AWG 14AWG 3/0)	
6.4 in (162.56 mm)	
4.12 in (104.65 mm)	
4.36 in (110.74 mm)	
80 %	
	40 A 3P L Unit mount 400 A 850 A Busbar connection line Busbar connection load 44.25 lbf.in (5 N.m) 0.000.15 in² (2.595 mm²) (AWG 14AWG 3/0) 6.4 in (162.56 mm) 4.12 in (104.65 mm) 4.36 in (110.74 mm)

Environment

Product certifications	CCC	
	IEC	
	CSA	
	CE	
	UL Listed	
Ambient air temperature for operation	104 °F (40 °C)	

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

Category	01120 - HL,JL UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Contraction warranty		
Warranty	18 months	