### Product data sheet Characteristics

# MPZB22T2FSS Mini Power Zone 22kVA 480D208Y120

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE D

Price\*: 28,896.00 USD



#### Main

Product	Sealed Transformer	
Certifications	UL Listed	
Туре	Mini Power-Zone	
Enclosure Code	CC	
Insulation Temperature	365 °F (185 °C)	
Phase	3 phase	
Primary Voltage	480 V	
Secondary Voltage	208Y/120 V	
Full Capacity Taps	2 5 % FCBN	
Power Rating	22.5 kVA	
Temperature Rise	115 °C	
Winding Material	Copper	
Interrupt Rating	18 kA	
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker	
Interior Type	NQ Panelboard interior	
Number of Spaces Available	24	
Number of Circuits	24	
Enclosure Type	NEMA 3R stainless steel 316	

#### Ordering and shipping details

Category	16276 - MPZ BOLT-ON BRANCH CB
Discount Schedule	PE2
Nbr. of units in pkg.	1
Package weight(Lbs)	670 lb(US) (303.91 kg)

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	No	
Packing Units		
Package 1 Height	1.21 ft (0.368 m)	
Package 1 width	2.43 ft (0.740 m)	
Package 1 Length	4.27 ft (1.302 m)	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
PVC free	Yes	

18 months

Warranty

# Product data sheet Dimensions Drawings

## MPZB22T2FSS

Approximate Dimensions

### Connections and Wiring Diagrams

