# Product data sheet Characteristics

## MJP36350

Circuit Breaker, PowerPact M, electronic trip, unit mount, 350A, 3 pole, 25 kA, 600 VAC, lugs off end







#### Main

Product or component type

		:
Complementary		
Line Rated Current	350 A	
Number of Poles	3P	
Breaking capacity code	J	
Magnetic tripping current	7003500 A	
Electrical connection	Lugs load Terminal nut line	:
Terminal identifier	AL800M23K	
Tightening torque	442.54 lbf.in (50 N.m) 0.150.37 in² (95240 mm²) (AWG 3/0500 kcmil)	
Height	12.86 in (326.6 mm)	
Width	0.32 in (8.06 mm)	:
Depth	8.27 in (210 mm)	
Continuous current rating	80 %	

Circuit breaker

#### Ordering and shipping details

Category	01205-MG, MJ UNIT MOUNT BREAKER	0 0
Discount Schedule	DE2	
Package weight(Lbs)	29.00 lb(US) (13.154 kg)	<u>.</u>
Returnability	Yes	. <u>u</u>
Country of origin	US	To the

#### Offer Sustainability

	, r
Sustainable offer status	Green Premium product

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	
PVC free	Yes	

### Contractual warranty

Warranty	18 months

#### **Approximate Dimensions**

