

# MPZB5S40FSS

## MINI PWR-ZONE DRY 1PH 5KVA

### 480V-120/240V



Price\* : 13,780.00 USD



#### Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	AA
Insulation Temperature	365 °F (185 °C)
Phase	1 phase
Primary Voltage	480 V
Secondary Voltage	120/240 V
Full Capacity Taps	2 5 % FCBN
Power Rating	5 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker
Interior Type	NQ Panelboard interior
Number of Spaces Available	10
Number of Circuits	10
Enclosure Type	NEMA 3R stainless steel 316

#### Ordering and shipping details

Category	16276-MPZ BOLT-ON BRANCH CB
Discount Schedule	PE2
Package weight(Lbs)	139.00 lb(US) (63.049 kg)
Returnability	No

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Packing Units

Package 1 Height	1.21 ft (0.368 m)
Package 1 width	1.59 ft (0.486 m)
Package 1 Length	3.72 ft (1.133 m)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

---

Approximate Dimensions

---

Connections and Wiring Diagrams

