MPZB15T2F25K MINI POWER-ZONE 25 AIC 15KVA

Product availability : Non-Stock - Not normally stocked in distribution facility

SQUARE D

Price* : 14,917.00 USD



Main

Main		
Product	Sealed Transformer	
Certifications	UL Listed	
Туре	Mini Power-Zone	
Enclosure Code	CC	
Insulation Temperature	365 °F (185 °C)	
Phase	3 phase	
Primary Voltage	480 V	
Secondary Voltage	208Y/120 V	
Full Capacity Taps	2 5 % FCBN	
Power Rating	15 kVA	
Temperature Rise	115 °C	
Winding Material	Copper	
Interrupt Rating	25 kA	
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker	
Interior Type	NQ Panelboard interior	
Number of Spaces Available	24	
Number of Circuits	24	
Enclosure Type	NEMA 3R hot-rolled steel	
Ordering and shipping details	i	
Category	16276 - MPZ BOLT-ON BRANCH CB	
Discount Schedule	PE2	
GTIN	00785901460985	
Nbr. of units in pkg.	1	

Ordering and shipping details

Category	16276 - MPZ BOLT-ON BRANCH CB	
Discount Schedule	PE2	
GTIN	00785901460985	
Nbr. of units in pkg.	1	

Jul 30, 2021



Package weight(Lbs)	550 lb(US) (249.48 kg)	
Returnability	No	
Country of origin	US	
Packing Units		
Package 1 Height	1.21 ft (0.368 m)	
Package 1 width	2.43 ft (0.740 m)	
Package 1 Length	4.27 ft (1.302 m)	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	

China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.

Compliant

Yes

Yes

Yes

18 months

EU RoHS Declaration

EU RoHS Directive

RoHS exemption information

China RoHS Regulation

Contractual warranty

Mercury free

PVC free

Warranty

MPZB15T2F25K

Approximate Dimensions

Product data sheet **Connections and Schema**

MPZB15T2F25K

Connections and Wiring Diagrams

