Product data sheet Characteristics

NF442L4TVS812C

Panelboard interior, NF, main lugs, 400A, Cu bus, 42 pole spaces, 3 phase, 4 wire, 600Y/347 VAC max, surge suppressor

Product availability: Non-Stock - Not normally stocked in distribution facility

SQUARE D

Price*: 28,325.46 USD



Main

Panelboard Type	Main lugs
Branch Circuit Breaker Type	EDB/EDG/EDJ
Busbar Material	Copper

Complementary

Complementary	
Number of spaces	42
Line Rated Current	400 A
[lu] rated interrupted current	25 kA
Wiring configuration	4-wire
Number of Phases	3 phase
Voltage Rating	600Y/347 V AC
Accessory Device	Surge protection device, 120 kA 400 V, 150 V
Connections - terminals	Lug line AWG 1/0750 kcmil aluminium Lug neutral AWG 1/0750 kcmil aluminium
Surge Capacity	60 kA between phase and neutral 60 kA between phase and ground 100 kA between neutral and ground
Tightening torque	274.99300.04 lbf.in (31.0733.90 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 274.99300.04 lbf.in (31.0733.90 N.m) 0.080.27 in² (53.48177.3 mm²) (AWG 1/0350 kcmil) 549.98 lbf.in (62.14 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 549.98 lbf.in (62.14 N.m) 0.080.24 in² (53.48152 mm²) (AWG 1/0300 kcmil) 375.01 lbf.in (42.37 N.m) 0.080.59 in² (53.48380 mm²) (AWG 1/0750 kcmil) 375.01 lbf.in (42.37 N.m) 0.080.24 in² (53.48152 mm²) (AWG 1/0300 kcmil)
Height	64 in (1625.60 mm)
Width	10.44 in (265.18 mm)

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Environment

Standards	CSA
	UL

Ordering and shipping details

09151 - NQ RTA PANELBOARDS
PE1A
00785901684541
1
7 lb(US) (3.18 kg)
No
US

Offer Sustainability

Offer Sustamability	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months