Product data sheet Characteristics

RLF36060U64AE1 POWERPACT R-FRAME, MOLDED CASE CIRCUIT BREAKER, 600V, 600A, 3P, 50kA







Main

Circuit breaker	
PowerPact R	
600 A	
Electronic, power, Micrologic 6.0 P, LSIG	
	PowerPact R 600 A

Complementary

Main		
Product or component type	Circuit breaker	
Range of product	PowerPact R	
Current sensor rating range	600 A	
Trip unit technology	Electronic, power, Micrologic 6.0 P, LSIG	
Complementary		
[le] rated operational current	600 A	
[Ue] rated operational voltage	600 V AC	
Mounting mode	Unit mount	
Poles description	3P	
Breaking capacity	125 kA 240 V AC 100 kA 480 V AC 50 kA 600 V AC	
Breaking capacity code	L	
Continuous current rating	80 %	
Electrical connection	Busbar connection line Busbar connection load	
Communication interface	Modbus	
Tightening torque	601.85 lbf.in (68 N.m) 0.080.62 in² (50400 mm²) (AWG 1/0750 kcmil) 601.85 lbf.in (68 N.m) 0.080.23 in² (50150 mm²) (AWG 1/0300 kcmil)	
Height	16.24 in (412.50 mm)	
Width	16.53 in (419.86 mm)	
Depth	14.49 in (368.05 mm)	
Environment		
Product certifications	UL Listed CSA IEC	

Environment

		ζ
Product certifications	UL Listed	
	CSA	Ē
	IEC	d
		<u>.</u>

Ordering and shipping details

Category	01245-RG,H,J,K,L,N UNIT MT BREAKERS
Discount Schedule	DE2
Package weight(Lbs)	52.00 lb(US) (23.587 kg)
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

<u></u>		
Warranty	18 months	