Product data sheet Characteristics

RLF36060CU44A POWERPACT R-FRAME, MOLDED CASE CIRCUIT BREAKER, 600V, 600A, 3P, 50kA





Price*: 35,061.00 USD



Main

Product or component type	Circuit breaker

Complementary

Complementary		7
Number of Poles	3P	. <u></u>
Electrical connection	Busbar connection line Busbar connection load	
Breaking capacity code	L	::
Tightening torque	601.85 lbf.in (68 N.m) 0.080.62 in² (50400 mm²) (AWG 1/0750 kcmil) 601.85 lbf.in (68 N.m) 0.080.23 in² (50150 mm²) (AWG 1/0300 kcmil)	ocici ocici
Height	16.24 in (412.50 mm)	
Width	16.53 in (419.86 mm)	
Depth	14.49 in (368.05 mm)	
Continuous current rating	100 %	

Ordering and shipping details

Category	01245-RG,H,J,K,L,N UNIT MT BREAKERS	
Discount Schedule	DE2	
Package weight(Lbs)	52.00 lb(US) (23.587 kg)	
Returnability	Yes	
Country of origin	US	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

^{*} Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Halogen content performance	Halogen free plastic parts product	
PVC free	Yes	
Circularity Profile	End of Life Information	
Environmental Disclosure	Product Environmental Profile	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	
RoHS exemption information	Yes	
Mercury free	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
REACh Regulation	REACh Declaration	

Contractual warranty

Warranty	18 months